(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 6 May 2005 (06.05.2005)

PCT

(10) International Publication Number WO 2005/040882 A1

(51) International Patent Classification7:

G02B 6/44

(21) International Application Number:

PCT/EP2003/010913

(22) International Filing Date:

30 September 2003 (30.09.2003)

(25) Filing Language:

English

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): PIRELLI & C. S.P.A. [IT/IT]; Via Gaetano Negri, 10, I-20123 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): PIZZORNO, Massimo [IT/IT]; Pirelli Cavi E Sistemi Telecom Holding S.p.A., Viale Sarca, 222, I-20126 Milano (IT). GINOC-CHIO, Alessandro [IT/IT]; Pirelli Cavi E Sistemi Telecom Holding S.p.A., Viale Sarca, 222, I-20126 Milano (IT). CONSONNI, Enrico [IT/IT]; Pirelli Cavi E Sistemi Telecom Holding S.p.A., Viale Sarca, 222, I-20126 Milano


- (74) Agents: COLOMBO, Stefano, Paolo et al.; Marchi & Partners S.r.l., Via Pirelli, 19, I-20124 Milano (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TELECOMMUNICATION LOOSE TUBE OPTICAL CABLE WITH REDUCED DIAMETER



(57) Abstract: It is described an optical fiber cable having an highly reduced diameter. The cable comprises: a central strength member (2); a number of tubes (3) containing loosely arranged optical fibers (4), each tube (3) having a thickness, each optical fiber having a coating; and a protective outer jacket (6), wherein the filling coefficient of optical fibers in at least one loose tube is $\geq 45^{\circ}/0$; the tubes comprise a material having an elasticity modulus ≥ 700 MPa; and the optical fibers are SM-R fibers having a microbending sensitivity \leq 4,0 dB. km⁻¹ / g. mm⁻¹ in a temperature range from about -30 °C to +60 °C at about 1550 nm.